




- Materials: nylon plastic
- Seals: nitrile rubber (NBR)
- Protection class: IP68-5 bar pressure (tighten parts, and use O- ring)
- Ambient temperature: -40 °C to 100 °C static
Short to 120 °C
Dynamic -20 °C to 80 °C
Short to 100 °C

- Delivery color: gray, black, other colors please ask

Note: Special size and type, please contact us

PG-Type:

AG (NPT)	Cable Range (mm)	Thread O.D. D1 (mm)	D2 (mm)	L1 (mm)	L2 (mm)	B1 (mm)	L3 (mm)	Spanner Size A&F(mm)
1/4	4-8	13.1	8.4	8	14.6	6.6	15.6	19/19
3/8	5-10	16.6	10.7	15	16.1	8.4	16.8	22/24
1/2	6-12	20.9	15.2	13	17.2	12.2	17.8	24/27
3/4	13-18	26.4	19.7	15	20	12.2	22	33/36
1	18-25	33.2	26.7	16	21.3	15	25.1	41
1 1/4	22-30	41.9	33.3	17	25.1	15	27.5	47/50
1 1/2	22-32	47.8	39.5	15	24.2	19	28.2	52/58
2	37-44	59.6	49.5	15	29.2	18.4	33.7	64/69